



定格荷重表

作業半径	最大作業半径				
	32.0m	36.0m	41.0m	45.0m	50.0m (オプション)
3.0m	16.0 t	16.0 t	16.0 t	14.5 t	10.0 t
4.0m				16.0 t	
15.5m				16.0 t	
16.0m				15.6 t	
17.0m				14.8 t	
18.0m				14.1 t	
19.0m				13.4 t	
20.0m				12.8 t	10.0 t
21.0m				12.1 t	9.5 t
22.0m			16.0 t	11.6 t	9.1 t
23.0m		16.0 t	15.2 t	11.0 t	8.6 t
24.0m	16.0 t	15.2 t	14.5 t	10.5 t	8.2 t
25.0m	15.3 t	14.5 t	13.9 t	10.0 t	7.8 t
26.0m	14.6 t	13.8 t	13.2 t	9.5 t	7.5 t
27.0m	13.9 t	13.1 t	12.6 t	9.0 t	7.1 t
28.0m	13.2 t	12.6 t	12.0 t	8.6 t	6.8 t
29.0m	12.6 t	12.0 t	11.5 t	8.2 t	6.4 t
30.0m	12.0 t	11.5 t	10.9 t	7.8 t	6.1 t
31.0m	11.5 t	11.0 t	10.4 t	7.4 t	5.8 t
32.0m	11.0 t	10.5 t	10.0 t	6.9 t	5.5 t
33.0m		10.1 t	9.5 t	6.5 t	5.3 t
34.0m		9.7 t	9.0 t	6.2 t	5.0 t
35.0m		9.3 t	8.6 t	5.9 t	4.7 t
36.0m		9.0 t	8.2 t	5.6 t	4.5 t
37.0m			7.9 t	5.3 t	4.3 t
38.0m			7.6 t	5.1 t	4.1 t
39.0m			7.4 t	4.9 t	3.9 t
40.0m			7.2 t	4.7 t	3.8 t
41.0m			7.0 t	4.5 t	3.7 t
42.0m				4.4 t	3.6 t
43.0m				4.3 t	3.5 t
44.0m				4.1 t	3.4 t
45.0m				4.0 t	3.3 t
46.0m					3.2 t
47.0m					3.2 t
48.0m					3.1 t
49.0m					3.1 t
50.0m					3.0 t

仕様

速巻上	16~27 t	33~128 m/min
起伏	103~107 sec	
旋回	0.44 rpm	
昇降	0.55 (0.66) m/min	
電巻上	110KW 4P 60%ED	インバータ制御
起伏	39KW 4P 25%ED	インバータ制御
旋回	19.5KW 4P 25%ED	インバータ制御
機昇降	22KW 4P CONT	
電源	400 (440) V 50 (60) Hz	
安全装置	巻過防止装置・過負荷防止装置 起伏制限装置・作業半径規制装置	

()内数値は、60Hzを示す。

